ECE 4750 Computer Architecture

Section 6: Problem-Based Learning on Processors

http://www.csl.cornell.edu/courses/ece4750 School of Electrical and Computer Engineering Cornell University

revision: 2022-09-29-23-30

List of Problems

1	Single-Cycle vs. Iterative Multipliers in a TinyRV1 Processor	2
	1.A Multiplication Microbenchmark	2
	1.B TinyRV1 Processor with Single-Cycle Integer Multiplier	3
	1.C TinyRV1 Processor with 4-Cycle Unpipelined Iterative Integer Multiplier	3
	1.D Comparison of Processor Microarchitectures	4

Problem 1. Single-Cycle vs. Iterative Multipliers in a TinyRV1 Processor

In this problem, we will consider a pipelined TinyRV1 processor that uses stalling to resolve data hazards. The baseline design includes a single-cycle integer multiplier and the alternative design includes a 4-cycle unpipelined iterative integer multiplier.

Part 1.A Multiplication Microbenchmark

We will evaluate the performance of both the baseline and alternative design by considering the following assembly sequence:

loop: lw x5, 0(x11) mul x6, x5, x12 sw x6, 0(x11) addi x11, x11, 4 addi x13, x13, -1 bne x13, x0, loop

Write a C function that clearly represents the functionality of this assembly sequence. Recall that arguments are passed in registers x11–x17, the return value is stored to x10, the return address is stored in x1, and x5–x7, x28–x31 are used as temporary registers.



Part 1.B TinyRV1 Processor with Single-Cycle Integer Multiplier

The baseline design uses a single-cycle integer multiplier. Assume that this processor has a cycle time of 1ns, and that the critical path is through the single-cycle multiplier in the X stage. **Draw a pipeline diagram illustrating the first iteration of the loop.** Draw arrows in your pipeline diagram to indicate any data or control hazards. **Fill in the appropriate row in the table in Part 1.D.** Assume that x13 is initially 64.

lw x5, 0(x11)														
mul x6, x5, x12														
sw x6, 0(x11)														
addi x11, x11, 4														
addi x13, x13, -1														
bne x13, x0, loop														

Part 1.C TinyRV1 Processor with 4-Cycle Unpipelined Iterative Integer Multiplier

The alternative design uses a 4-cycle unpipelined iterative integer multiplier. Assume that multiplier is no longer on the critical path, and the cycle time for the processor decreases to 0.75ns. **Draw a pipeline diagram illustrating the first iteration of the loop.** Draw arrows in your pipeline diagram to indicate any data or control hazards. **Fill in the appropriate row in the table in Part 1.D.** Assume that x13 is initially 64.

lw x5, 0(x11)														
mul x6, x5, x12														
sw x6, 0(x11)														
addi x11, x11, 4														
addi x13, x13, -1														
bne x13, x0, loop														

Part 1.D Comparison of Processor Microarchitectures

Consider the results in the following table. Which microarchitecture has the highest performance on this microbenchmark? How would these results generalize to other workloads? Discuss some of the trade-offs in terms of area and energy between the processor microarchitectures. Consider what would happen if we used a 4-cycle *pipelined* integer multiplier.

Microarchitecture	Inst/Prog	Cycles/Inst (ns)	Time/Cycle	Exec Time (ns)				
Processor w/ 1-cycle Mul			1.0ns					
Processor w/ 4-cycle Mul			0.7ns					